

FIBERMAD MADERA WOOD

Escalera de tijera industrial barnizada TA Varnished Industrial A-frame ladder



Equipamiento estándar Standard equipment

- Escalera de doble subida fabricada en madera de pino.
Double-sided ladder made of pine wood.
- Bisagras en acero de espesor 2,5 mm con sistema antiapertura.
Hinges made of 2.5 mm thick steel with anti-opening system.
- Tacos de goma antideslizante.
Non-slip rubber feet.
- Cadena antiapertura.
Anti-opening chain.
- Distancia entre peldaños de 28 cm.
28 cm distance between steps.
- Peldaño plano con huella de 70 mm.
Flat step with a 70 mm. tread.
- Barnizada.
Varnished

DATOS. Escalera de tijera industrial TA DATA. Industrial A-frame ladder TA

REF.						
T4A	4	1,24	1,19	0,34	0,47	6
T5A	5	1,52	1,45	0,34	0,50	7
T6A	6	1,80	1,72	0,34	0,53	8
T7A	7	2,08	1,99	0,34	0,56	9
T8A	8	2,36	2,26	0,34	0,59	11
T9A	9	2,64	2,52	0,34	0,62	13
T10A	10	2,92	2,79	0,34	0,65	16
T12A	12	3,48	3,06	0,34	0,71	22
T14A	14	4,04	3,33	0,34	0,77	26
T16A	16	4,60	3,59	0,34	0,83	31
T17A	17	4,88	3,86	0,34	0,86	36



Tacos antideslizantes para repuesto.
Non-slip rubber feet for replacement.